2сн **РоЕ NVR**

Features

32ch High Definition PoE NVR supporting recording and playback resolutions up to 8 megapixels on each channel.

All NYX recorders are built around the most advanced SOC technology to ensure outstanding performance and reliability of the system.

Integrated with 16 PoE network ports supporting Plug & Play IP Camera connection to the NVR, simultaneous 16ch playback, and 4K high definition display output.

Easy thumbnail and advanced Intelligence Analytics search capabilities means finding the footage you need takes seconds, not hours! The perfect choice for meeting the demands of your security requirements.

Time -Slice Search

The fastest method of finding video footage. Simply click on any thumbnail image to start instant playback. Find what you're looking for in seconds - not hours!

Push Notifications Have your NVR alert you to intrusions or events by *pushing notifications* straight to your smartphone. Playback the event within seconds for peace-of-mind

and quick response!



IP-X32P



Specifications

System	Compression	H.265
	Operating System	Embedded Linux
	Performance	Pentaplex: preview, record, playback, backup
		and remote access
Video	Network Input	32 Channel IPC input
	Global Bitrate	256Mbs
	Input Resolution	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P @25 / 30fps
	Output	HDMI x1: 4K, 1080P, 1280x1024 / VGA x1: 1080P, 1280x1024
Audio	Network Input	32 Channel IPC audio input
	2-way Audio	RCA x1
	Local Output	RCA x1
Record	Record Stream	Dual Stream recording
	Resolution	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P
	Mode	Manual, Timer, Motion, Sensor
Playback	Playback	Max 16 Channel Simultaneous
	Search	Time Slice / Time / Event / Sensor
	Function	Play, pause, FF, FB, digital zoom
	Mode	Manual, Sensor, Motion, Exception
Alarm	Input	16 Channel local alarm input, support IPC alarm input
	Output	4 Channel
	Triggering	Record, Snap, Email, Preset
Network	Interface	RJ45 x1 : 10/100/1000 Mbps
	PoE Port	RJ45 x16
	Protocol	TCP/IP, DHCP, DNS, DDNS, UPnP, NTP, SMTP, PPPoE
	Remote Access	Max 10 users online
Smartphone		iOS, Android
Storage	HDD	SATA x8, e-SATA x1 : Max 10TB per HDD
Backup	Backup	USB Flashdrive, USB mobile HDD, Network
Ports	USB	USB 2.0 x1 (front panel), USB 3.0 x1 (rear panel)
Other	Accessories	Mouse, Remote Control, Rack Mount Hardware
	Power Consumption	≤ 15W (without HDD) 240V
	Dimensions (mm)	430(W) x 450(D) x 90(H)
	Working Environment	-10°C ~ 50°C 10% ~ 90% humidity

Intelligence Analytics

Get **FAST** search results by configuring in-built image analytic algorithms.

Supports Tripwire, Abandoned Object, Missing Object, Video Exception & Intrusion.











•



4K Output Network



Mobile

CMS



E-mail

PARADISE SECURITY AUSTRALIA PTY LTD

P: (07) 5549 2911

ЪоЕ

PoE

www.paradisesecurity.com.au